

DRILL HOLE # Rock Core Characterization

Project No. 2000-10-220

Location: Whitby, Ontario
Direction: Vertical Bearing: 230 Dip: 13
Manufacturer's Drill Designation:
Drilling Contractor: ABC Diamond Drilling
Logged By: MJF Date: 02/10/2000

Date Hole Started: 1899-12-30 Finished: 1899-12-30
Elevation: 0
X Coordinate: 440 m Y Coordinate: 684 m
Drilling Method: Diamond Bit Core: 5aposds+ Casing:
Fluid: Baroid mud Cased To:

Depth (m)	Run	Core no.	Symbols	LITHOLOGIC DESCRIPTION	Instrumentation	Degree of Weathering	Rock Hardness	Point Load Strength (MPa)	UU Shear Strength (MPa)	Discontinuity Data			Core Recovery % 25 50 75	RQD % 25 50 75	RMR
										Dip Angles ■ 30 60 ■	Type	Spacing (mm)			
1	1	C1		Sandy, brown, Clay Till.		III		45	24						
2				Grey, medium to fine grained, crystalline Limestone, interbedded with dark grey shale.											
3															
4															
5															
6															
7															
8															
9															
10															
11															
12															
13															
14															
15															
16				2											
17															
18															
19															
20															
21															
22															
23	III	2.8	52			37									
24															
25															
26															
27															
28															
29															
30	IV		52	48											
31															

Your Company
Information Here

Client:
Project:
Sheet: 1 of 2

DRILL HOLE # Rock Core Characterization

Project No. 2000-10-220

Location: Whitby, Ontario
Direction: Vertical Bearing: 230 Dip: 13
Manufacturer's Drill Designation:
Drilling Contractor: ABC Diamond Drilling
Logged By: MJF Date: 02/10/2000

Date Hole Started: 1899-12-30 Finished: 1899-12-30
Elevation: 0
X Coordinate: 440 m Y Coordinate: 684 m
Drilling Method: Diamond Bit Core: 5aposds+ Casing:
Fluid: Baroid mud Cased To:

Depth (m)	Run	Core no.	Symbols	LITHOLOGIC DESCRIPTION	Instrumentation	Degree of Weathering	Rock Hardness	Point Load Strength (MPa)	UU Shear Strength (MPa)	Discontinuity Data			Core Recovery % 25 50 75	RQD % 25 50 75	RMR
										Dip Angles ■ 30 60 ■	Type	Spacing (mm)			
31	2	C2													
32															
33						III	3.5	76	32						
34															
35															
36							3.7								
37															
38															
39															
40	3	C3				III	4.1	112	48						
41															
42															
43							3.8								
44															
45															
46						I	2.1	98	54						
47															
48															
49							1.8								
50															
51															
52															
53	4	C4		Interbedded, pale green, Dolomite and dark brown dolomitic Limestone. Slightly fractured, fresh.		II	1.6	121	47						
54															
55															
56							2.3	148							
57															
58															
59				End of Borehole											
60															

Your Company
Information Here

Client:
Project:
Sheet: 2 of 2